

Features

Standard Features	Easily Configured To Meet Your Needs	Options & Accessories
<p>Measurements</p> <p>GS-2669 DC</p> <ul style="list-style-type: none"> 9.70 m (31 ft 9 in) working height Up to 680 kg (1,500 lbs) lift capacity <p>GS-3369 DC</p> <ul style="list-style-type: none"> 11.75 m (38 ft 6 in) working height Up to 454 kg (1,000 lbs) lift capacity <p>GS-4069 DC</p> <ul style="list-style-type: none"> 14.12 m (46 ft 3 in) working height Up to 363 kg (800 lbs) lift capacity <p>Productivity</p> <ul style="list-style-type: none"> Drive at full height AC sealed drive motors Folding guardrails with full height swing-gate Smart Link™ control system (joystick, 2 lift speeds & 2 selectable proportional drive speeds, user-friendly diagnostics) Platform control with battery charge indicator and diagnostic display On-board diagnostic system AC power to platform Front oscillating axle Positive traction control Regenerative braking Tilt level sensor with audible alarm Descent alarm Flashing LED beacons Horn Hour meter Telematics-Ready Connector <p>Power</p> <ul style="list-style-type: none"> 48 V DC battery pack 	<p>Platform</p> <ul style="list-style-type: none"> 2.79 x 1.60 m (9 ft 2 in x 5 ft 3 in) steel frame platform with replaceable aluminium deck 1.52 m (5 ft) slide-out extension deck <p>Outrigger Options</p> <ul style="list-style-type: none"> Automatic levelling hydraulic outriggers⁽¹⁾ No outriggers (standard) <p>Power Options</p> <ul style="list-style-type: none"> 48 V DC (eight 6 V batteries), 225 Ah (standard on GS-2669 DC & GS-3369 DC) 48 V DC (eight 6 V batteries), 315 Ah (standard on GS-4069 DC) <p>Drive</p> <ul style="list-style-type: none"> 2 x 4 <p>Axle</p> <ul style="list-style-type: none"> Front oscillating axle <p>Tyres</p> <ul style="list-style-type: none"> Foam-filled, non-marking rough terrain 	<p>Productivity Options</p> <ul style="list-style-type: none"> Air line to platform Power to platform plug, socket with optional Residual-current Circuit Breaker with Overcurrent protection Biodegradable hydraulic oil Track & Trace ⁽¹⁾ (GPS unit providing machine location & operating information) Motion alarm <p>Power Options</p> <ul style="list-style-type: none"> Low temperature cut-out module 48 V DC (eight 6 V batteries), 315 Ah - on GS-2669 DC & GS-3369 DC
		

⁽¹⁾ Includes a first 2 years subscription